

SAFETY DATA SHEET

RONSON BUTANE REFILL

1. IDENTIFICATION OF THE PREPARATION AND THE COMPANY

Product Name: Ronson Butane Refill
Synonyms, Trade Names: Butane Fuel 90ml to 400ml
Applications: Gas lighter fuel
Supplier: Ronson International Ltd.
International House, Old Brighton Road,
Lowfield Heath. Crawley, West Sussex. RH11 0QN
Emergency Telephone: 01293 843600 (office hours only)

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient Name	CAS No	Contents	Health (class)	Risk (R No.)
Butane	106 - 97 - 8	99%		

Composition Comments Substances indicating a hazard do so under EC Directives 88/379 & 67/548
Aerosol classified as Flammable

3. HAZARDS IDENTIFICATION

Flammable
Substances not indicating a health hazard may have **Occupational Exposure Limits detailed in Section 8 of this data sheet**
Ingredients are below the levels to cause the product to be classified

4. FIRST AID MEASURES

General: Note! Keep affected person away from heat, sparks and flames!
Eyes: Promptly wash eyes with water while lifting the eyelids. Get medical attention immediately. Continue to rinse. Burns should be flushed with water to normalise temperature. Cover eyes with sterile dressing. Do NOT apply ointments or powder.
Skin: Remove affected person from source of contamination. Promptly stop exposure and get medical attention if frostbite has occurred. Promptly flush contaminated skin with soap or mild detergent and water. Promptly remove clothing if penetrated and flush the skin with water.
Inhalation: Move the exposed person to fresh air at once. Perform artificial respiration if breathing has stopped. When breathing is difficult, properly trained personnel may assist affected person by administering 100% oxygen. Keep the affected person warm and at rest. Get prompt medical attention
Ingestion: NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS.
DO NOT induce vomiting Get medical attention immediately.

5. FIRE FIGHTING MEASURES

Extinguishing Media Stop flow of material to fire. Fire can be extinguished using foam, dry chemicals, and sand dolomite etc.

Special Fire Fighting Procedures

Use water to keep fire exposed cool and disperse vapours. Cool containers exposed to flames with water from side until well after fire is out. Move container from fire area if it can be done without risk.

SAFETY DATA SHEET

RONSON BUTANE REFILL

Vapour Pressure (mmHg)	1520 @ 18°C	Vapour Density (air = 1)	2.05
Melting Point	-137 °C		
Flash Point	-60 °C	Flash Point Method	CC (closed cup)
Auto ignition Temperature	405 °C		
Flammability Limit	lower % 1.90		
Flammability Limit	upper % 8.50		

10. STABILITY AND REACTIVITY

Stability	Avoid heat, sparks and flames
Materials to avoid	Strong oxidizing agents
Conditions to avoid	Evaporates easily in air. Reacts strongly with oxidizers.

Hazardous Decomposition Products

Toxic gases/vapours/fumes of carbon monoxide (CO) carbon dioxide (CO₂)

11. TOXICOLOGICAL INFORMATION

Toxic Conc.-LC50	680 ppm/2h (inh - mus)
Target organs	Central nervous system, eyes, respiratory system and lungs
Health Warnings	Gas or vapour displaces oxygen available for breathing (asphyxiant). Narcotic effect
Medical Symptoms	May cause suffocation. Dizziness.
Acute and chronic health hazards	Contact with liquid form may cause frostbite.

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

Disposal Methods	Vent to atmosphere
Empty Containers	Dispose of empty containers without puncturing DO NOT INCINERATE

14. TRANSPORT INFORMATION

ROAD:

UN No	1950	Hazchem Code	2WE
ADR Class	2	ADR Item No.	3b
ADR Hazard No.	23 Flammable Gas		
CEFIC TEC ® No.	276	ADR Label No.	3
Label for conveyance			

SAFETY DATA SHEET

RONSON BUTANE REFILL

AIR:

UN No. 1950 Air Transport Class No. 2
AIR Sub Class 3

SEA:

UN No. 1950 Sea Transport Class No. 2(2.1)

RAIL:

Rail Transport Class No 2 Road PT. 3b

15. REGULATORY INFORMATION

Label for Supply

Risk Phrases R 10 **Flammable**

Safety Phrases S - 9 Keep container in well ventilated place
S - 16 Keep away from sources of ignition - **NO SMOKING**
S - 33 Take precautionary measures against Static discharges

16. OTHER INFORMATION

-User Notes This product is supplied in an aerosol form using a highly flammable gas as a propellant. Properly used for the intended purpose and in accordance to this safety data sheet should not present any undue hazard.

Information Sources Dangerous Properties of Industrial Chemicals, 6.edition, N.Sax,1984
OSHA Air Contaminants - Permissible Exposure Limits (Title 29)
Handbook of Toxic and Hazardous Chemicals and Carcinogens, Sittig,'85
Hazardous Materials, Emergency Response Guidebook, DOT-P 5800.3, 1984
NIOSH/OSHA Pocket Guide to Chemical Hazards (latest edition)
Threshold Limit Values and Biological Exposure Indices for 1994 - 95
Chemical Safety Data Guide. Bureau of National Affairs , 1985

SDS No: 1001
Revision Date: January 2011
Revision No./Replaces: SDS issued 01 09 95
Revision Comments: New Safety Data to CHIP format